TPL Series

TPL121500SFR Datasheet

12V Front Terminal VRLA-AGM



Specifications

Voltage (Vdc)	12V
Ah Capacity (8HR to 1.75VPC @25°C)	148
Ah Capacity (20HR to 1.75VPC @25°C)	159.8
Ah Capacity (8HR to 1.80VPC @25°C)	145.6
Max Charge Current (A)	45
Max Discharge Current (A)	800
Short Circuit Current (A)	2477 (5 sec)
Internal Resistance (mΩ)	Approx. 4.1 Ω
Terminal Type	I2 thread lead alloy terminal to accept M6 bolt
Terminal Torque	51.7±10.3 Kgf·cm / 44.9±9.0 Lbf·in / 5.1±1.0 N·m
Container Material	Flame Retardant ABS (UL 94-V0)
Weight (kg. / lb.)	Approx. 46.5kg / 102.51lb
Length (L) (mm / in)	551.0 ± 2.5mm / 21.69 ± 0.10in
Width (W) (mm / in)	110.0 ± 1.5mm / 4.33 ± 0.06in
Height (H) (mm / in)	288.0 ± 2.5mm / 11.33 ± 0.10in
Design Life	Up to 15 Years in Standby Service @ 20°C. Eurobat (20°C): >12 Years Very Long Life
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F - 122°F) Charge / Storage -15°C - 40°C (5°F - 104°F)
Float Charging Voltage	13.5 - 13.8 Vdc/battery @ 25°C (77°F)
Eq. Charging Voltage	14.4 - 15.0 Vdc/battery @ 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months & 10 months with equalization charge @ 25°C (77°F). Full recharge required before use. Charge sooner if stored above 25°C (77°F).

KEY FEATURES

- Valve Regulated Lead Acid (VRLA) Battery
- Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%
- Pure Lead Construction and Proprietary Elements

APPLICATIONS

- Designed for Float Service Standby Power Applications

SAFETY & COMPLIANCE

- Built in Accordance with IEC 60896-21/22:2004
- UL1973 Listed (MH66728)
- UL1989 Recognized (MH14533)
- Certified by TUV NORD according to ISO 9001:2015

MH14533

UL CERTIFIED SAFETY US MH66728

© 2026 CSB Energy Technology Co., Ltd. All Rights Reserved.
CSB Energy Technology Co., Ltd. reserves the right to change specifications or design without notice. Visit csb-battery.com for the latest information.

11F, No. 150, Sec. 4, Chengde Rd., Shilin Dist., Taipei City 111052, Taiwan (R.O.C.)
Tel: +886-2-2880-5600 Mail: service@csb-battery.com.tw

TPL Series

TPL121500SFR Datasheet

12V Front Terminal VRLA-AGM


Constant Current Discharge Characteristics Per Battery: Amperes (25°C / 77°F)

F.V/Time	15MIN	30MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
10.02V (1.67VPC)	262	176	106	76.3	60.0	42.7	33.5	27.8	23.8	18.7	15.5	8.14
10.50V (1.75VPC)	230	162	102	75.0	59.1	42.1	33.0	27.4	23.5	18.5	15.3	7.99
10.80V (1.80VPC)	205	150	97.1	73.1	57.5	41.1	32.3	26.8	23.1	18.2	15.1	7.92

Constant Power Discharge Characteristics Per Battery: Watts (25°C / 77°F)

F.V/Time	15MIN	30MIN	60MIN	90MIN	2HR	3HR	4HR	5HR	6HR	8HR	10HR	20HR
10.02V (1.67VPC)	2718	1894	1182	880	695	497	392	326	281	221	185	94.1
10.50V (1.75VPC)	2504	1782	1145	866	684	490	387	322	277	219	182	92.6
10.80V (1.80VPC)	2287	1655	1098	840	665	479	379	317	273	216	181	91.9

Line Drawing



© 2026 CSB Energy Technology Co., Ltd. All Rights Reserved.
CSB Energy Technology Co., Ltd. reserves the right to change specifications or design without notice. Visit csb-battery.com for the latest information.

11F, No. 150, Sec. 4, Chengde Rd., Shilin Dist., Taipei City 111052, Taiwan (R.O.C.)
Tel: +886-2-2880-5600 Mail: service@csb-battery.com.tw